

NURAJACK TECHNICAL DATA SHEET

PRODUCT DETAILS

Product Description	Nurajacks are an adjustable, self-levelling pedestal support system for tile, paving or timber decking over exterior membrane waterproofing. The system consists of:
	 Nurajack Adjustable pedestal with self-levelling head in multiple sizes from 28mm to 550mm Nurajack Star.t and Nurapad offer low profile solutions starting from 8mm in height Accessories include: Nuragrid Tile Cladding Clip (5mm, 10mm, 15mm, 20mm) for use between wall/balustrade and tile/paver Adjustment Key Shims (1mm, 2mm or 3mm) For a full list of accessories, visit www.nurajack.co.nz.
Scope of use	Nurajacks can be used within the scope of NZBC E2/AS1. Nurajacks can be installed over Concrete, Ply or Enertherm insulated substrates with a membrane. Nurajacks can also be installed over concrete patio or other suitable substrates to facilitate level threshold doorways.
	Nurajacks are compatible with all sheet membranes (eg. Butyl, TPO, Bitumen etc.) and are installed without penetration of the membrane.
	Nurajacks are suitable for new or existing commercial and residential buildings.
Company Name	Nuralite Group Ltd
Contact name & details	Lewis Olding Nuralite waterproofing Ltd 60D Leon Leicester Ave Mt Wellington
	Auckland ph (09) 579 2046

Date: November 2025 nuralite.co.nz



Product names/Name of PTS	Nurajack SE Nurajack Star.T Nurapad Nurapad Shim Nuragrid
Level of assurance which is met by	
In service history (NZ & overseas)	1000's of residential and commercial projects around New Zealand. Some examples include:
	Sugar Tree Apartments Auckland
	Sky City Auckland
	Heritage Hotel Auckland To the First State of Technology
	Taupo Water Treatment Plant National Library Wallington
	National Library Wellington

Conditions

New Zealand Building Code	New Zealand Building Code Clause E2 Pages 54 & 55 Codemark BCS-151216-CMNZ
Design guidelines	 Tiled and Timber decks must be enclosed with a parapet or balustrade. See www.nurajack.co.nz/downloads for detail drawings and specifications.
Installation requirements	See www.nurajack.co.nz for full installation details.
Maintenance requirements	Periodic checking for loose Nurajacks especially if the substrate has moved.
Warranty	20-year product warranty.

Other company information

Date: November 2025 nuralite.co.nz



Environmental	ISO 14001, LEED Credits
Quality assurance	
Groups company is a member of	

Sign off:

The information above is true and accurate. All test results are available upon request and I have not withheld anything that could result in the product complying with the identified performance clauses of the NZ building code.

Nuralite Group Ltd. accepts any and all liability arising from reliance upon the information contained in this document and replicated on the Masterspec PTS template.

Signed:

Title: Managing Director

The information in this product data sheet is based on our experience and testing. It represents the latest information available at the time of printing, but no guarantee of its accuracy is made or implied, nor responsibility taken for use to which this information may be put. We reserve the right to alter or up-date information parameters and formulations at any time without notice.